

# GiuliettaX

## PL2SVX



### TECHNICAL FEATURES

2 L58E groups compatible with  
LELIT58 barista tools

Double HX System for group heating with  
thermosiphonic circulation

Rotative pump

LCD display with black background

Possibility to activate the pre-infusion, the cleaning  
cycle and the notification for the water filter change

Programmable automatic dosing on each group

Temperature displayed in degrees  
Celsius or Fahrenheit

Operating temperatures programmable  
thanks to the LTS (LELIT Thermal Stability)

Dose counter for each group and for single button

Active Coffee delivery timer and ECO Mode

Double manometer for pump/steam pressure

Water supply and direct discharge

Stainless steel appliance body with textured  
cup warmer rack and removable side panels

Anti-burn multidirectional steam and  
hot water wands

Double keyboard for coffee delivery

Mug friendly

Adjustable feet

Two groups coffee machine  
with exceptional performance,  
configurable to efficiently  
meet the needs of every  
professional user.

The machine is versatile,  
performing, highly reliable  
and easy to use and  
maintain.

---

**Copper boiler:** 10 l

**Dimensions LxDxH:** 58x56x46 cm

**Weight:** 47 kg

---

### DELIVERED WITH

2 LELIT58 2-ways filterholder with classic  
polished black handle and Coffee Slide spout

LELIT58 1 dose filter (9-11 g), IMS

2 LELIT58 2 doses filter (14-18 g), IMS

LELIT58 blind filter, IMS

Tamper

2 cup racks

Small brush with nylon bristles

---

PL2SVX-EU	230 V 50 Hz   Plug Type E+F
PL2SVX-AUS-4180	220-240 V 50/60 Hz   Plug Type I
PL2SVX-CUS	120 V 60 Hz   Plug Type B
PL2SVX-UK	220-240 V 50/60 Hz   Plug Type G